

# HJSIL® 200 Hydrophilic Fumed Silica



HJSIL® 200 is a kind of hydrophilic fumed silica with a specific surface area of 200 m<sup>2</sup>/g. It's high purity white colloidal powder.

- 1.Reinforcement filler in elastomers.
- 2.Rheology and thixotropy control of liquid systems, binders, polymers, etc.
- 3.Used as anti-settling, thickening, anti-sagging agent.
- 4.Improvement of free flow and anti-caking characteristics of powders.

## CHARACTERISTIC

HJSIL® 200 is a kind of hydrophilic fumed silica with a specific surface area of 200 m<sup>2</sup>/g. It's high purity white colloidal powder.

### Properties

Reinforcement filler in elastomers

Rheology and thixotropy control of liquid systems, binders, polymers, etc.

Used as anti-settling, thickening, anti-sagging agent

Improvement of free flow and anti-caking characteristics of powders

High transparency

## TECHNICAL DATA

Properties and test methods	Unit	Typical Value	Standardization
Specific surface area (BET)	m <sup>2</sup> /g	200 ± 25	GB/T10722
pH value (in 4% dispersion)		3.6 ~ 4.5	GB/T1717
Loss on drying (2 hours at 105°C)	Wt%	≤ 1.5	GB/T5211.3
Loss on ignition (2 hours at 1000°C, based on material dried for 2 hours at 105°C)	Wt%	≤ 2.5	GB/T20020
Sieve residue (45 μm)	%	≤ 0.05	GB/T5211.14
Silica content (based on ignited material)	Wt%	≥ 99.8	GB/T20020
Tamped density (based on material dried for 2 hours at 105°C)	g/L	40 ~ 60	GB/T5211.4
Carbon content (based on material dried for 2 hours at 105°C)	Wt%	≤ 0.2	GB/T20020

## APPLICATIONS

- HTV and RTV silicone rubber
- Adhesives and sealants
- Paints, coatings and pigments
- Printing inks
- Cable compounds
- Unsaturated polyester resins, laminated resins and Gel coats